

Reserve Studies | Insurance Appraisals | Wind Mitigation

COMMERCIAL WINDSTORM MITIGATION REPORT (OIR-B1-1802)

Key Manor Condominium Association, Inc. 3122 30th Ave N, Building A, Units 101-105, 201-205 St. Petersburg, FL 33713



As of 7/22/2019 FPAT File# MUD1913508

FELTEN PROFESSIONAL ADJUSTMENT TEAM 866.568.7853 www.FPATadjusters.com | info@FPATadjusters.com



RECAPITULATION OF MITIGATION FEATURES For 3122 30th Ave N, Building A, Units 101-105, 201-205

1. <u>Building Code:</u> Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1974 per Pinellas County

Property Appraiser.

2. Roof Covering: FBC Equivalent

Comments: The roof covering was replaced in 2003. The roof permit was

confirmed and the permit number is 03-10000353. This roof was verified as meeting the building code requirements outlined on the

mitigation affidavit.

3. Roof Deck Attachment: Other

Comments: Inspection verified a roof deck composed of lightweight concrete

gypsum panels supported by steel bar joists.

4. Roof to Wall Structural

Attachment:

Comments: Inspection verified a roof-wall connection composed of steel bar

joists structurally connected to the wall/support system.

5. Roof Geometry: Flat Roof

Comments: Inspection verified a flat roof shape.


6. SWR: No

Comments: Secondary water resistance does not apply to light weight concrete

roof decks.

7. Opening Protection: None or Some Glazed Openings

Comments: Inspection verified no opening protection.









Exterior Elevation



Roof Construction








Roof Construction

Roof Construction









Roof Construction



Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 7/22/2019					
Owner Information					
Owner Name: Key Manor Condominium A	Owner Name: Key Manor Condominium Association, Inc. Contact Person: Jenny Kidd				
Address: 3122 30th Ave N, Building A, Units 101-105, 201-205		Home Phone:			
City: St. Petersburg	Zip: 33713	Work Phone: (727) 726-8000			
County: Pinellas		Cell Phone:			
Insurance Company:		Policy #:			
Year of Home: 1974	# of Stories: 2	Email:			

NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.

1.	Building Code : Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in
	the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?
	A. Built in compliance with the FBC: Year Built . For homes built in 2002/2003 provide a permit application with a date after
	3/1/2002: Building Permit Application Date (MM/DD/YYYY)
	B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, and 1996
	provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)//
[X	C. Unknown or does not meet the requirements of Answer "A" or "B"
2.	Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number

Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.

2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
[] 1. Asphalt/Fiberglass Shingle				[]
[] 2. Concrete/Clay Tile				[]
[] 3. Metal				[]
[X] 4. Built Up			2003	[]
[] 5. Membrane				[]
[] 6. Other				[]

- [X] A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.
- [] B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.
- [] C. One or more roof coverings do not meet the requirements of Answer "A" or "B".
- D. No roof coverings meet the requirements of Answer "A" or "B".
- 3. **Roof Deck Attachment**: What is the weakest form of roof deck attachment?
- [] A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.
- [] B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials Property Address 3122 30th Ave N, Building A, Units 101-105, 201-205, St. Petersburg

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

	or greate 182 psf.	er resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
[] D.		d Concrete Roof Deck.
		teel bar joist
		or unidentified.
[] G.	No attic ac	ccess.
5	feet of the i	Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within nside or outside corner of the roof in determination of WEAKEST type)
[] A.	Toe Nails	[] Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
		[] Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
M	inimal con	ditions to qualify for categories B, C, or D. All visible metal connectors are:
		[]Secured to truss/rafter with a minimum of three (3) nails, and []Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the
ПЪ	Clina	blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
[] D.	Clips	[] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
П С.	Single Wra	
	~g	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
[] D.	Double W	
		[] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
[X] E	E. Structura	al Anchor bolts structurally connected or reinforced concrete roof.
	Other:	
	Unknown No attic ac	or unidentified excess
		try: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of ture over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
[] A.	Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter:
[X] E	3. Flat Roo	
[] C.	Other Roo	
[] A.	SWR (also sheathin from wa 3. No SWR	Vater Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the ag or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling atter intrusion in the event of roof covering loss.

Inspectors Initials Property Address 3122 30th Ave N, Building A, Units 101-105, 201-205, St. Petersburg

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Glazed Openings				Non-Glazed Openings	
		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure						
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	B Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
	Opening Protection products that appear to be A or B but are not verified						
N	Other protective coverings that cannot be identified as A, B, or C						
X No Windborne Debris Protection							

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

☐ A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

	or X in the table above
	☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
[]	B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings
	are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the
	product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for
	"Cyclic Pressure and Large Missile Impact" (Level B in the table above):

☐ A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N,

- ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile 4.5 lb.)
- SSTD 12 (Large Missile 4 lb. to 8 lb.)
- For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)

B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist

1 0	, ,	1 0		
B.2 One or More Non-Glazed openings classified as Le	vel D in the table above, a	and no Non-Glazed	openings classified as Lev	vel C, N, or X
in the table above				

B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

[]	C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSE
	meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

☐ C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist	
3	

C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 3122 30th Ave N, Building A, Units 101-105, 201-205, St. Petersburg

[☐] C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

FPAT File	#MIID1	191	135	508
-----------	--------	-----	-----	-----

[] N. Exterior Opening Protection (unverified shutter sys					
"B" with no documentation of compliance (Level N		r systems that appear to meet Answer A or			
☐ N.1 All Non-Glazed openings classified as Level A, B, C, o	N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist				
 N.2 One or More Non-Glazed openings classified as Level I table above 	D in the table above, and no No	on-Glazed openings classified as Level X in the			
☐ N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above				
$[X] \ \underline{\textbf{X. None or Some Glazed Openings}} \ \text{One or more Glazed}$	openings classified and Lev	vel X in the table above.			
MITIGATION INSPECTIONS MUST E Section 627.711(2), Florida Statutes, prov					
Qualified Inspector Name: John Felten	License Type: CBC	License or Certificate #: CBC1255984			
Inspection Company: Felten Professional Adjustment To	eam, LLC.	Phone: 866-568-7853			
Qualified Inspector – I hold an active license as a	: (check one)				
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board					
 □ Building code inspector certified under Section 468.607, Florida □ General, building or residential contractor licensed under Section 					
$\hfill \Box$ Professional engineer licensed under Section 471.015, Florida St	atutes.				
☐ Professional architect licensed under Section 481.213, Florida St	atutes.				
Any other individual or entity recognized by the insurer as posses verification form pursuant to Section 627.711(2), Florida Statutes		ons to properly complete a uniform mitigation			
Licensees under s.471.015 or s.489.111 may authorize a direct experience to conduct a mitigation verification inspection. I, am a qualified inspector and contractors and professional engineers only) I had my employand I agree to be responsible for his/her work.	I personally performed the	e inspection or (licensed			
Je At					
Qualified Inspector Signature:Dat	e: <u>7/22/2019</u>				
An individual or entity who knowingly or through gross ness is subject to investigation by the Florida Division of Insural appropriate licensing agency or to criminal prosecution. (Secretifies this form shall be directly liable for the misconduct performed the inspection.	nce Fraud and may be sub ection 627.711(4)-(7), Flor	ject to administrative action by the ida Statutes) The Qualified Inspector who			
Homeowner to complete: I certify that the named Qualified	d Inspector or his or her emp	sloyee did perform an inspection of the			
residence identified on this form and that proof of identification	n was provided to me or my	Authorized Representative.			
Signature:I	Date:				
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to who the first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes only and cannot b hurricanes.	oe used to certify any product or	construction feature as offering protection from			

Inspectors Initials Property Address 3122 30th Ave N, Building A, Units 101-105, 201-205, St. Petersburg

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.